ELSEVIER

Nuclear Engineering and Design 174 (1997) 369–370

Nuclear Engineering and Design

Author Index of Volume 174

Albertini, C., Material properties for reactor pressure vessels and containment shells under dynamic loading 174 (1997) 135
Almeida, M.C.F., see Venancio-Filho, F. 174 (1997) 165

Bieniussa, K.W., H. Reck and H. Hübel, Determination of more realistic $K_{e,r}$-factors for simplified elastic–plastic analysis 174 (1997) 343
Blauel, J.G., see Schmitt, W. 174 (1997) 237
Breitbach, G., see Wolters, J. 174 (1997) 353
Brückner-Foit, A., see Hojo, K. 174 (1997) 247
Butler, S., Semi-probabilistic fracture mechanics approach for a quality assurance system for welds of a containment for a 1000 MW nuclear power unit 174 (1997) 177

Cepeda, V., see López, A. 174 (1997) 157
Chang, H.S., see Kim, J.T. 174 (1997) 51
Choi, Y.H., see Kim, Y.J. 174 (1997) 69
Choi, Y.H., Y.K. Chung, Y.W. Park, J.B. Lee and G. Wilkowski, Development of new Z-factors for the evaluation of the circumferential surface crack in nuclear pipes 174 (1997) 3
Chung, Y.K., see Choi, Y.H. 174 (1997) 3
Costaz, J.L. and R. Danisch, Discussion on recent concrete containment designs 174 (1997) 189
Cowan, R.L., see Horn, R.M. 174 (1997) 313

Dameron, R.A., see López, A. 174 (1997) 157
Danisch, R., see Costaz, J.L. 174 (1997) 189
de Barros, F.C.P., see Venancio-Filho, F. 174 (1997) 165

Ferreira, W.G., see Venancio-Filho, F. 174 (1997) 165
Ford, F.P., see Horn, R.M. 174 (1997) 313

Galon, P., see Studer, E. 174 (1997) 119
Gebert, A., F. Schneider and K. Mummert, Influence of oxide structure on the elevated temperature pitting behaviour of Fe-Cr-Ni alloys 174 (1997) 327
Gordon, G.M., see Horn, R.M. 174 (1997) 313
Gotoh, N., see Kashima, K. 174 (1997) 33

Hirano, M., see Yagawa, G. 174 (1997) 91
Hofstötter, P., see Oppermann, W. 174 (1997) 287
Hojo, K., I. Muroya and A. Brückner-Foit, Fracture toughness transition curve estimation from a notched round bar specimen using the local approach method 174 (1997) 247
Hong, S.-Y., I.-S. Jeong and T.E. Jin, Recent strategy and progress in Korean nuclear PLIM program 174 (1997) 25
Horn, R.M., G.M. Gordon, F.P. Ford and R.L. Cowan, Experience and assessment of stress corrosion cracking in L-grade stainless steel BWR internals 174 (1997) 313
Hübel, H., see Bieniussa, K.W. 174 (1997) 343
Hwang, I.S., see Kim, J.H. 174 (1997) 17

Ishiwata, M., see Kashima, K. 174 (1997) 33

Jeong, I.-S., see Hong, S.-Y. 174 (1997) 25
Jin, T.E., see Hong, S.-Y. 174 (1997) 25
Jun, H.K., see Kim, Y.J. 174 (1997) 69

Kanno, S., see Kashima, K. 174 (1997) 33
Kashima, K., N. Miura, S. Kanno, K. Miyazaki, M. Ishiwata and N. Gotoh, A research program for dynamic fracture evaluation of Japanese carbon steel pipes 174 (1997) 33
Kawaguchi, S., N. Sakamoto, G. Takano, F. Matsuda, Y. Kikuchi and L. Mráz, Microstructural changes and fracture behavior of CF8M duplex stainless steels after long-term aging 174 (1997) 273
Keller, H.P., see Oppermann, W. 174 (1997) 287
Kemnitz, P., U. Richter and H. Klüber, Measurements of the acoustic field on austenitic welds: a way to higher reliability in ultrasonic tests 174 (1997) 259
Kikuchi, M., Study on the effect of the crack length on the J_{IC} value 174 (1997) 41
Kikuchi, Y., see Kawaguchi, S. 174 (1997) 273
Kim, I.-S., see Kim, J.-W. 174 (1997) 59
Kim, J.H. and I.S. Hwang, Crack shape evolution of surface flaws under fatigue loading of austenitic pipes 174 (1997) 17

PII S0029-5493(97)00249-5

Kim, J.T., H.K. Kwon, H.S. Chang and Y.W. Park, Improvement of impact toughness of the SA 508 class 3 steel for nuclear pressure vessel through steel-making and heat-treatment practices 174 (1997) 51
Kim, J.-W. and I.-S. Kim, Effect of dynamic strain aging on the leak-before-break analysis in SA106 Gr.C piping steel 174 (1997) 59
Kim, Y.J., M.W. Suh, H.K. Jun, Y.W. Park and Y.H. Choi, Development of expert system for nuclear piping integrity 174 (1997) 69
Kim, Y.J., see Yu, Y.J. 174 (1997) 101
Kleinöder, W. and F. Otremba, Analysis and repair of cracking in partition plate of RHR heat exchanger at Brunsbüttel nuclear power station 174 (1997) 293
Klenk, A., see Kußmaul, K. 174 (1997) 219
Klüber, H., see Kemnitz, P. 174 (1997) 259
Kulak, R.F., P.A. Pfeiffer and E.J. Plaskacz, Modeling of containment structures on high performance computers 174 (1997) 143
Kußmaul, K., A. Klenk, T. Link and M. Schüle, Dynamic material properties and their application to components 174 (1997) 219
Kwon, H.K., see Kim, J.T. 174 (1997) 51

Lee, J.B., see Choi, Y.H. 174 (1997) 3
Link, T., see Kußmaul, K. 174 (1997) 219
López, A., V. Cepeda, I. Maldonado and R.A. Dameron, Ultimate capacity of a mark II primary containment using new probabilistic failure criteria 174 (1997) 157

Maldonado, I., see López, A. 174 (1997) 157
Matsuda, F., see Kawaguchi, S. 174 (1997) 273
Miura, N., see Kashima, K. 174 (1997) 33
Miyazaki, K., see Kashima, K. 174 (1997) 33
Mráz, L., see Kawaguchi, S. 174 (1997) 273
Mummert, K., see Gebert, A. 174 (1997) 327
Muroya, I., see Hojo, K. 174 (1997) 247

Nickel, H., see Wolters, J. 174 (1997) 353

Oppermann, W., P. Hofstötter and H.P. Keller, Long-term installations of the DC-potential drop method in four nuclear power plants and the accuracies thereby obtained for monitoring of crack initiation and crack growth 174 (1997) 287
Otremba, F., see Kleinöder, W. 174 (1997) 293

Park, K.B., see Yu, Y.J. 174 (1997) 101
Park, S.H., see Yu, Y.J. 174 (1997) 101
Park, Y.W., see Choi, Y.H. 174 (1997) 3
Park, Y.W., see Kim, J.T. 174 (1997) 51
Park, Y.W., see Kim, Y.J. 174 (1997) 69
Pellkofer, D., see Schmidt, J. 174 (1997) 301
Pfeiffer, P.A., see Kulak, R.F. 174 (1997) 143
Plaskacz, E.J., see Kulak, R.F. 174 (1997) 143

Reck, H., see Bieniussa, K.W. 174 (1997) 343
Richter, U., see Kemnitz, P. 174 (1997) 259
Rödig, M., see Wolters, J. 174 (1997) 353

Sakamoto, N., see Kawaguchi, S. 174 (1997) 273
Schmidt, J., D. Pellkofer and E. Weiß, Alternative methods for postweld treatment of austenitic pipe welds to increase the operational safety of BWR plants 174 (1997) 301
Schmitt, W., D.Z. Sun and J.G. Blauel, Damage mechanics analysis (Gurson model) and experimental verification of the behaviour of a crack in a weld-cladded component 174 (1997) 237
Schneider, F., see Gebert, A. 174 (1997) 327
Schüle, M., see Kußmaul, K. 174 (1997) 219
Shibata, K., Progress of LWR structural safety research at JAERI 174 (1997) 79
Soneda, N., see Yagawa, G. 174 (1997) 91
Stadtmüller, W. and D. Sturm, Leak-before-break behaviour of austenitic and ferritic pipes containing circumferential defects 174 (1997) 327
Studer, E. and P. Galon, Hydrogen combustion loads—plexus calculations 174 (1997) 119
Sturm, D., see Stadtmüller, W. 174 (1997) 327
Suh, M.W., see Kim, Y.J. 174 (1997) 69
Sun, D.Z., see Schmitt, W. 174 (1997) 237

Takano, G., see Kawaguchi, S. 174 (1997) 273

Venancio-Filho, F., F.C.P. de Barros, M.C.F. Almeida and W.G. Ferreira, Soil-structure interaction analysis of NPP containments: substructure and frequency domain methods 174 (1997) 165

Wallin, K., Re-evaluation of thermal shock experiment results based on the VTT approach for statistical treatment of fracture toughness data 174 (1997) 205
Weiß, E., see Schmidt, J. 174 (1997) 301
Wilkowski, G., see Choi, Y.H. 174 (1997) 3
Wolters, J., G. Breitbach, M. Rödig and H. Nickel, Investigation of the ratcheting phenomenon for dominating bending loads 174 (1997) 353

Yagawa, G., S. Yoshimura, N. Soneda and M. Hirano, Probabilistic fracture mechanics analyses of nuclear pressure vessels under PTS events 174 (1997) 91
Yoon, K.S., see Yu, Y.J. 174 (1997) 101
Yoshimura, S., see Yagawa, G. 174 (1997) 91
Yu, Y.J., K.S. Yoon, S.H. Park, K.B. Park and Y.J. Kim, Extended applications of LBB piping evaluation diagrams for a new plant design 174 (1997) 101

ELSEVIER

Nuclear Engineering and Design 174 (1997) 371–372

Nuclear Engineering and Design

Subject Index of Volume 174

Engineering mechanics

Study on the effect of the crack length on the J_{IC} value
M. Kikuchi 174 (1997) 41
Material properties for reactor pressure vessels and containment shells under dynamic loading
C. Albertini 174 (1997) 135
Damage mechanics analysis (Gurson model) and experimental verification of the behaviour of a crack in a weld-cladded component
W. Schmitt, D.Z. Sun, J.G. Blauel 174 (1997) 237
Fracture toughness transition curve estimation from a notched round bar specimen using the local approach method
K. Hojo, I. Muroya, A. Brückner-Foit 174 (1997) 247
Measurements of the acoustic field on austenitic welds: a way to higher reliability in ultrasonic tests
P. Kemnitz, U. Richter, H. Klüber 174 (1997) 259
Experience and assessment of stress corrosion cracking in L-grade stainless steel BWR internals
R.M. Horn, G.M. Gordon, F.P. Ford, R.L. Cowan 174 (1997) 313
Determination of more realistic $K_{e,r}$-factors for simplified elastic-plastic analysis
K.W. Bieniussa, H. Reck, H. Hübel 174 (1997) 343
Investigation of the ratcheting phenomenon for dominating bending loads
J. Wolters, G. Breitbach, M. Rödig, H. Nickel 174 (1997) 353

Materials properties

Development of new Z-factors for the evaluation of the circumferential surface crack in nuclear pipes
Y.H. Choi, Y.K. Chung, Y.W. Park, J.B. Lee, G. Wilkowski 174 (1997) 3
Study on the effect of the crack length on the J_{IC} value
M. Kikuchi 174 (1997) 41
Material properties for reactor pressure vessels and containment shells under dynamic loading
C. Albertini 174 (1997) 135
Modeling of containment structures on high performance computers
R.F. Kulak, P.A. Pfeiffer and E.J. Plaskacz 174 (1997) 143
Damage mechanics analysis (Gurson model) and experimental verification of the behaviour of a crack in a weld-cladded component
W. Schmitt, D.Z. Sun, J.G. Blauel 174 (1997) 237
Fracture toughness transition curve estimation from a notched round bar specimen using the local approach method
K. Hojo, I. Muroya, A. Brückner-Foit 174 (1997) 247
Measurements of the acoustic field on austenitic welds: a way to higher reliability in ultrasonic tests
P. Kemnitz, U. Richter, H. Klüber 174 (1997) 259
Experience and assessment of stress corrosion cracking in L-grade stainless steel BWR internals
R.M. Horn, G.M. Gordon, F.P. Ford, R.L. Cowan 174 (1997) 313
Influence of oxide structure on the elevated temperature pitting behaviour of Fe-Cr-Ni alloys
A. Gebert, F. Schneider, K. Mummert 174 (1997) 327
Determination of more realistic $K_{e,r}$-factors for simplified elastic-plastic analysis
K.W. Bieniussa, H. Reck, H. Hübel 174 (1997) 343
Investigation of the ratcheting phenomenon for dominating bending loads
J. Wolters, G. Breitbach, M. Rödig, H. Nickel 174 (1997) 353

Mechanical design, component fabrication and testing

Development of new Z-factors for the evaluation of the circumferential surface crack in nuclear pipes
Y.H. Choi, Y.K. Chung, Y.W. Park, J.B. Lee, G. Wilkowski 174 (1997) 3

PII S0029-5493(97)00250-1

Crack shape evolution of surface flaws under fatigue loading of austenitic pipes
J.H. Kim and I.S. Hwang 174 (1997) 17
A research program for dynamic fracture evaluation of Japanese carbon steel pipes
K. Kashima, N. Miura, S. Kanno, K. Miyazaki, M. Ishiwata and N. Gotoh 174 (1997) 33
Improvement of impact toughness of the SA 508 class 3 steel for nuclear pressure vessel through steel-making and heat-treatment practices
J.T. Kim, H.K. Kwon, H.S. Chang, Y.W. Park 174 (1997) 51
Effect of dynamic strain aging on the leak-before-break analysis in SA106 Gr.C piping steel
J.-W. Kim and I.-S. Kim 174 (1997) 59
Development of expert system for nuclear piping integrity
Y.J. Kim, M.W. Suh, H.K. Jun, Y.W. Park, Y.H. Choi 174 (1997) 69
Progress of LWR structural safety research at JAERI
K. Shibata 174 (1997) 79
Probabilistic fracture mechanics analyses of nuclear pressure vessels under PTS events
G. Yagawa, S. Yoshimura, N. Soneda, M. Hirano 174 (1997) 91
Extended applications of LBB piping evaluation diagrams for a new plant design
Y.J. Yu, K.S. Yoon, S.H. Park, K.B. Park, Y.J. Kim 174 (1997) 101
Hydrogen combustion loads—plexus calculations
E. Studer and P. Galon 174 (1997) 119
Modeling of containment structures on high performance computers
R.F. Kulak, P.A. Pfeiffer and E.J. Plaskacz 174 (1997) 143
Ultimate capacity of a mark II primary containment using new probabilistic failure criteria
A. López, V. Cepeda, I. Maldonado, R.A. Dameron 174 (1997) 157
Soil-structure interaction analysis of NPP containments: substructure and frequency domain methods
F. Venancio-Filho, F.C.P. de Barros, M.C.F. Almeida, W.G. Ferreira 174 (1997) 165
Semi-probabilistic fracture mechanics approach for a quality assurance system for welds of a containment for a 1000 MW nuclear power unit
S. Butler 174 (1997) 177
Discussion on recent concrete containment designs
J.L. Costaz and R. Danisch 174 (1997) 189
Re-evaluation of thermal shock experiment results based on the VTT approach for statistical treatment of fracture toughness data
K. Wallin 174 (1997) 205
Dynamic material properties and their application to components
K. Kußmaul, A. Klenk, T. Link, M. Schüle 174 (1997) 219
Microstructural changes and fracture behavior of CF8M duplex stainless steels after long-term aging
S. Kawaguchi, N. Sakamoto, G. Takano, F. Matsuda, Y. Kikuchi, L. Mráz 174 (1997) 273
Long-term installations of the DC-potential drop method in four nuclear power plants and the accuracies thereby obtained for monitoring of crack initiation and crack growth
W. Oppermann, P. Hofstötter, H.P. Keller 174 (1997) 287
Analysis and repair of cracking in partition plate of RHR heat exchanger at Brunsbüttel nuclear power station
W. Kleinöder, F. Otremba 174 (1997) 293
Influence of oxide structure on the elevated temperature pitting behaviour of Fe-Cr-Ni alloys
A. Gebert, F. Schneider, K. Mummert 174 (1997) 327
Leak-before-break behaviour of austenitic and ferritic pipes containing circumferential defects
W. Stadtmüller, D. Sturm 174 (1997) 335

Miscellaneous

Foreword 174 (1997) 1
Announcement 174 (1997) 111
Preface 174 (1997) 117
Announcement 174 (1997) 197

Nuclear safety

Recent strategy and progress in Korean nuclear PLIM program
S.-Y. Hong, I.-S. Jeong and T.E. Jin 174 (1997) 25
Development of expert system for nuclear piping integrity
Y.J. Kim, M.W. Suh, H.K. Jun, Y.W. Park, Y.H. Choi 174 (1997) 69
Progress of LWR structural safety research at JAERI
K. Shibata 174 (1997) 79